

## 01711 SIP B16 Bench Pillar Drill 450w 12-speed



**Part No:** 01711

**Price:** £199.99 (exc VAT) Save £137.21

(RRP £337.20) | £239.99 (inc VAT)

### Specifications

01711 SIP B16 Bench Pillar Drill 450w 12-speed - 16mm Drilling Capacity (Mild Steel)

The SIP B16 12-Speed 450w Bench Pillar Drill makes light work of preparing and finishing workpiece materials including ferrous and non-ferrous metals, woods and plastics.

Using an adjustable tilting table, the drill can be easily positioned to enable accurate drilling.

#### Features

12 spindle speeds powered by a 450w motor from a 230v (13A) supply

Supports a variety of drilling applications

High-power brushless induction motor

Fitted with drilling depth stop

Adjustable drill table for greater accuracy

Safety interlock switch for safe motor belt adjustment

SIP 2-Year Standard Silver Warranty

Applications & uses: Suitable for ferrous and non-ferrous metals, woods and plastics, pilot, blind and general drilling applications, small bracketry, and home and small workshop metalwork and woodwork.

Supports a variety of drilling applications

Compatible with materials including ferrous and non-ferrous metals, hard and soft woods and high-density plastics.

Multi-speed functionality

Allows precise control of hole sizes across the drilling spectrum.

High-power brushless induction motor

Delivers powerful performance for consistent high-quality drilling.

Intuitive features for ease-of-use

Adjustable drilling table and three-lever handle ensures smooth drilling force.

Fitted with drilling depth stop

Accurately maintains a quality of repetitive or blind hole drilling, helping to minimise material wastage.

Safety interlock switch

Allows the user to adjust the motor belt with confidence knowing the drill cannot start-up accidentally.

Specifications

Input Voltage: 230v (13A)

Motor Power: 450w

No. of Speeds: 12 speeds

Speed Range: 300rpm - 2550rpm

Drill Bit Size: 3mm - 16mm

Spindle Taper: B16

Table Size: 195mm x 200mm

Base Size: 340mm x 205mm

Column Diameter: Ø 58mm

Swing: 260mm

Height: 840mm

Spindle Travel: 60mm

Collar Diameter: Ø 58mm

Max. Distance: 350mm (chuck to table)

470mm (chuck to base)