

## 01714 SIP Pro F16 Floor Pillar Drill 550w 16-speed



**Part No:** 01714

**Price:** £339.99 (exc VAT) Save £233.21

(RRP £573.20) | £407.99 (inc VAT)

### Specifications

01714 SIP Pro F16 Floor Pillar Drill 550w 16-speed - 16mm Drilling Capacity (Mild Steel)

The SIP Pro F16 16-Speed 550w Floor Pillar Drill makes light work of preparing and finishing a variety of workpiece materials including ferrous and non-ferrous metals, woods and plastics.

Using an adjustable tilting table and tilt scale, the drill can be easily positioned for accurate drilling.

#### Features

16 spindle speeds powered by a 550w motor from a 230v (13A) supply

Supports a variety of drilling applications

High-power brushless induction motor

Fitted with drilling depth stop

Adjustable drill table for greater accuracy

Safety interlock switch for safe motor belt adjustment

SIP 2-Year Standard Silver Warranty

Applications & uses: Suitable for ferrous and non-ferrous metals, woods and plastics, pilot, blind, batch and general drilling applications, manufacturing gates, rails and trailers, plus metalwork and woodwork environments.

Supports a variety of drilling applications

Compatible with materials including ferrous and non-ferrous metals, hard and soft woods and high-density plastics.

Multi-speed functionality

Allows precise control of hole sizes across the drilling spectrum.

High-power brushless induction motor

Delivers powerful performance for consistent high-quality drilling.

Intuitive features for ease-of-use

Adjustable drilling table and three-lever handle ensures smooth drilling force.

Fitted with drilling depth stop

Accurately maintains a quality of repetitive or blind hole drilling, helping to minimise material wastage.

Safety interlock switch

Allows the user to adjust the motor belt with confidence knowing the drill cannot start-up accidentally.

Specifications

Input Voltage: 230v (13A)

Motor Power: 550w

No. of Speeds: 16 speeds

Speed Range: 220rpm - 2800rpm

Drill Bit Size: 3mm - 16mm

Spindle Taper: MT2

Table Size: 250mm x 250mm

Base Size: 460mm x 270mm

Column Diameter: Ø 72mm

Swing: 316mm

Height: 1570mm

Spindle Travel: 80mm

Collar Diameter: Ø 72mm

Max. Distance: 663mm (chuck to table)

1150mm (chuck to base)