

Carpenter Goodwin
31 Bridge St
Leominster
Herefordshire
HR6 8DU
01568 616266
www.carpentergoodwin.co.uk

## 06825 SIP SUB 3075-SS Heavy-Duty Dirty Water Pump



Part No: 06825

Price: £129.99 (exc VAT) Save £92.61

(RRP £222.60) | £155.99 (inc VAT)

## **Specifications**

06825 SIP SUB 3075-SS Heavy-Duty Dirty Water Pump

The SIP SUB 3075-SS Heavy-Duty Dirty Water Pump is ideal for draining dirty water from water tanks and vessels, work sites and large ponds.

The pump is suited for heavy-duty use as a temporary or permanent fixture.

Water pumps can help prevent costly damage to property or work areas from recurring rainwater or groundwater and can also be used for a variety of agricultural and commercial maintenance purposes.

**Features** 

Powerful 750w/1hp brushless induction motor

26-10-2025 1/3

Fitted float switch prevents pump from running dry

Max. 8mtr pumping head for quick draining

Drains dirty water with particles up to Ø 35mm

Lightweight and compact design

SIP 2-Year Standard Silver Warranty

Applications & uses: Quickly drains flooded areas.

Suitable for agricultural or commercial environments.

Designed as a temporary or permanent fixture.

Powerful brushless induction motor (750w/1hp)

Draws water at a max. flow rate of 275ltr/min through an impeller at the pump base.

The heavy-duty wound motor is durable and lightweight.

Fitted float switch

Ensures the pump functions unaided when the activation depth (495mm) is reached.

This prevents the pump from running dry and overheating when in use.

Max. 8mtr pumping head

Discharges water flow to a max. height of 8mtr through hose or pipe connected to the pump outlet.

This ensures the intended area or item is drained quickly.

Particle capacity

Suitable for draining dirty water with particles to max. diameter of 35mm.

Lightweight, compact design

Includes a carry handle for portability and lowering into water (7mtr max. operating depth).

A mounted power cable hook provides added safety.

Stainless steel housing

Hard-wearing, durable casing ensures it withstands the demanding environments it is intended for.

High-grade carbon steel pump shaft

High-tensile strength compound for long life use.

Power cable

Fitted with a 10mtr length cable for greater versatility.

26-10-2025 2/3

Specifications

nput Supply: 230v 50Hz

Motor Power: 750w (1hp)

Flow Rate: 275ltr/min

Outlet: 25mm Ø - 40mm Ø 1" BSP

Max. Pumping Head: 8mtr

Max. Operating Depth: 7mtr

Max. Particle Diameter: Ø 35mm

Max. Water Temperature: 35°C

Body Type: Stainless Steel

Pump Type: Dirty Water

Cable Length: 10mtr

Protection: IPX8

26-10-2025 3/3