

06865 SIP SUB 3040 Submersible Water Pump



Part No: 06865

Price: £49.99 (exc VAT) Save £35.41 (RRP £85.40) | £59.99 (inc VAT)

Specifications

06865 SIP SUB 3040 Submersible Water Pump

The SIP SUB 3040 Water Pump is ideal for draining clean water from a flooded cellar, basement, small water or collection tank, work site, well, or hot tub.

Clean water is considered to be free from large particle contamination.

Water pumps can help prevent costly damage to property or work areas from recurring rainwater or groundwater.

This pump can also be used for a variety of garden maintenance purposes and is suited for intermittent use.

Features

Powerful 400w/0.5hp brushless induction motor

Fitted float switch prevents pump from running dry

Max. 6mtr pumping head for quick draining

Drains water with particles up to Ø 3mm

Lightweight and compact design

SIP 2-Year Standard Silver Warranty

Applications & uses: Quickly drains flooded areas. Effective for a variety of garden maintenance purposes. Suitable for domestic or light commercial use. Intended for intermittent use.

[SIP 2-Year Standard Silver Warranty | Find out more](#)

Powerful brushless induction motor (750w/1hp)

Draws water at a max. flow rate of 150ltr/min through an impeller at the pump base. The heavy-duty wound motor is durable and lightweight.

Fitted float switch

Ensures the pump functions unaided when the activation depth (360mm) is reached. This prevents the pump from running dry and overheating when in use.

Max. 6mtr pumping head

Discharges water flow to a max. height of 6mtr through hose or pipe connected to the pump outlet. This ensures the intended area or item is drained quickly.

Particle capacity

Suitable for draining water with particles to max. diameter of 3mm.

Lightweight, compact design

Includes a carry handle for portability and lowering into water (7mtr max. operating depth). A mounted power cable hook provides added safety.

High-grade carbon steel pump shaft

High-tensile strength compound for long life use.

Power cable

Fitted with a 9mtr length cable for greater versatility.

Specifications

Input Supply: 230v 50Hz

Motor Power: 400w (0.5hp)

Flow Rate: 150ltr/min

Outlet: 25mm Ø - 40mm Ø 1" BSP

Max. Pumping Head: 6mtr

Max. Operating Depth: 7mtr

Max. Particle Diameter: Ø 3mm

Max. Water Temperature: 35°C

Body Type: Plastic

Pump Type: Clean Water

Cable Length: 9mtr

Protection: IPX8