

## Hypertherm Powermax45 XP Plasma Cutter 230V Single Phase



**Part No:** 088130

**Price:** £1995.95 (exc VAT) Save £861.19  
(RRP £2857.14) | £2395.14 (inc VAT)

### Specifications

**Hypertherm Powermax45 XP Plasma Cutter Hand System with 6.1m (20ft) Torch 230V Single Phase**

**Special Price £1950.00 (Exc Vat) RRP £2857.14 (Exc Vat) - In Stock**

Meet our best-selling 008130 Powermax® portable plasma system.

The Powermax45® XP delivers increased cut capacity – up to 22 mm (7/8") metal.

Enjoy faster cut speeds and automatic gas adjustment for quick, simple setup and operation.

Material Severance up to 29mm (1 1/8").

Consumable changes allow you to switch between standard cutting, light gouging & metal marking.

Mains 240v single phase - Engine driven generator requirement 12.5KVA or 10kW.

CPC Port.

New Duramax® Lock torches support handheld and mechanized cutting of a wider range of metal thicknesses, along with enhanced gouging and marking capabilities.

### **Operator benefits**

Patented drag-cutting technology makes the Powermax45 XP easy to use - even for first-time operators.

Smart Sense technology ensures that air pressure is always correctly set. 17% faster cutting with 11% greater cutting efficiency, the superior cut and gouge quality reduces grinder cleaning up times.

New torch design for improved performance and allows for faster and easier consumables changing operations.

Consumables last 70-140% longer than competitor's products.

**Powermax45 XP applications**

- Drag cutting • Extended Reach cutting • Extended Reach gouging • Fine Feature cutting
- Flush cutting • Marking • Max control gouging • Mechanised cutting • Precision gouging

**Easy to use**

- Small size and light weight provide exceptional portability for a 22 mm (7/8") rated cutting system
- Patented drag-cutting technology makes the Powermax45 XP easy to use - even for first-time operators
  - Smart Sense™ technology ensures that air pressure is always correctly set

<b>Capacity</b>	<b>Thickness</b>	<b>Cut Speed</b>
	Cutting	
Recommended	16mm (5/8")	500mm/min (20ipm)
	22mm (7/8")	250mm/min (10ipm)
Severance (hand cutting)	2900 (1 1/8")	125mm/min (5 ipm)
Pierce	12mm (1/2")	
<b>Capacity</b>	<b>Metal removal rate</b>	<b>Groove profile</b>
Typical gouge	3/4kg (7.5lbs) per hour	3.2mm (1/8") D x 6.8mm (5/16") W

**Hypertherm short overview Video**

**Hypertherm Powermax45 XP Demonstration video:**

## Optional Extras

### 05709 SIP Welding & Cutting Table



**Part No:** 05709

**Price:**

£129.99 (exc  
VAT)

£155.99 (inc  
VAT)