

## 7010CC0 Coupling 20mm x 20mm



**Part No:** 7010CC0

**Price:** £6.40 (exc VAT) | £7.68 (inc VAT)

### Specifications

7010CC0 Coupling 20mm x 20mm for water fitting

#### Benefits

- Tried and tested
- Proven reliability
- Simple to use
- Robust in the extreme
- Simplifying the job
- Best in its class

#### Application

- Metric polyethylene pipes

## Technical information

### CHEMICAL RESISTANCE:

Plasson fittings are supplied, as standard, with polyacetal split rings and NBR 'O' rings which are suitable for water.

For aggressive chemical applications, PVC split rings and EPDM or FPM 'O' rings can be supplied to produce a better chemical resistance

### OPERATING PRESSURES:

Plasson mechanical fittings are tested and approved by WRAS in the UK to PN 16.

Other standard bodies that have tested and approved plasson fittings include:

KIWA (NL), standard institution of Israel (IL), QAS (AS/NZS 4129) (AUS), Santens provningsanstalt Stockholm (S),

Statens Planmerk (S), SGWA (CH), Byggningsreglementet (DK), DVGW (DIN 8076 part 3) (D), IIP (UNI9561) (IT)

### OPERATING TEMPERATURES:

Not suitable for hot water, however, will withstand sub zero temperatures

Connection 20 x 20 mm