

7010CC0 Coupling 20mm x 20mm



Part No: 7010CC0

Price: £6.40 (exc VAT) | £7.68 (inc VAT)

Specifications

7010CC0 Coupling 20mm x 20mm for water fitting

Benefits

- Tried and tested
- Proven reliability
- Simple to use
- Robust in the extreme
- Simplifying the job
- Best in its class

Application

- Metric polyethylene pipes

Technical information

CHEMICAL RESISTANCE:

Plasson fittings are supplied, as standard, with polyacetal split rings and NBR 'O' rings which are suitable for water.

For aggressive chemical applications, PVC split rings and EPDM or FPM 'O' rings can be supplied to produce a better chemical resistance

OPERATING PRESSURES:

Plasson mechanical fittings are tested and approved by WRAS in the UK to PN 16.

Other standard bodies that have tested and approved plasson fittings include:

KIWA (NL), standard institution of Israel (IL), QAS (AS/NZS 4129) (AUS), Santens proviningsanstalt Stockholm (S),

Statens Planmerk (S), SGWA (CH), Bygningsreglementet (DK), DVGW (DIN 8076 part 3) (D), IIP (UNI9561) (IT)

OPERATING TEMPERATURES:

Not suitable for hot water, however, will withstand sub zero temperatures

Connection 20 x 20 mm