

Carpenter Goodwin
31 Bridge St
Leominster
Herefordshire
HR6 8DU
01568 616266
www.carpentergoodwin.co.uk

Aspen 2 FRT 2 stroke petrol 5ltr



Part No: ASPEN2T5L

Price: £20.42 (exc VAT) | £24.50 (inc VAT)

Specifications

ASPEN2T5L Aspen 2 FRT 2 stroke petrol 5ltr

Collection only - We will not deliver or ship this product.

Aspen 2 is an alkylate petrol pre-mixed at 50:1 ratio with a premium quality biodegradable 2-stroke oil.

Aspen 2 is suitable for use in chainsaws, clearing saws, hedge trimmers, power cutters and other land-based 2-stroke engines.

Aspen 2 is virtually free from harmful substances such as benzene, aromatic hydrocarbons or olefins; substances that can cause serious health problems.

Aspen Alkylate Petrol also keeps the spark plugs and combustion chamber of your machine cleaner as

1-07-2025 1/2

it burns cleaner than pump Petrol fuels containing Ethanol.

Aspen fuel also protects against problems associated with using E5 & E10 Ethanol pump Petrol fuels and Aspen fuels has a far longer usable life than E5 or E10.

Aspen fuels can be stored and remain stable with a usable volatility for 5 years, which means your machines start easier and perform better even after long periods of storage.

Aspen is a superior quality fuel and emits 99% less toxic emissions so always choose Aspen for less harmful emissions and fuel system protection.

Aspen 2 is virtually free from harmful substances such as benzene, aromatic hydrocarbons or olefins; substances that can cause serious health problems.

Aspen Alkylate Petrol also keeps the spark plugs and combustion chamber of your machine cleaner as the fuel burns more cleanly.

There are numerous environmental benefits of Aspen fuels, such as reducing the formation of ground-level ozone (smog) by about 40%.

The oil in Aspen 2 has been selected for its performance benefits. It is fully synthetic with as much as 60% renewable content. It is biodegradable and free from ash and solvents.

The oil in Aspen 2 contributes to an extremely clean engine and has optimum lubrication characteristics at all engine temperatures.

1-07-2025 2/2