

Carpenter Goodwin
31 Bridge St
Leominster
Herefordshire
HR6 8DU
01568 616266
www.carpentergoodwin.co.uk

## Food grade clear grease spray 500ml



Part No: CG90H1

**Price:** £9.04 (exc VAT) | £10.85 (inc VAT)

## **Specifications**

Food Grade CG-90 is clear grease with an extreme pressure P.T.F.E. additive. Food Grade CG-90 is clear and clean in application. Food Grade CG-90 is ideal for general bearing lubrication and those parts that require lubrication where water, steam, and high humidity are present. When P.T.F.E. is used as a lubricant additive it reduces friction, wear, and reduces the energy consumption of driving machinery. P.T.F.E has the lowest coefficient of friction of any solid material and this adds greatly to the effectiveness of the grease. Stick slip behaviour is also reduced by the P.T.F.E. Food Grade CG-90 is a premium product which is effective through a wide temperature range from -40°C to +200°C (applies to base product before aerosol packing). Food

Specifications range from -40°C to +200°C (applies to base product before aerosol packing). Food Grade CG-90 clear grease lubricant with PTFE is resistant to most acid and alkalis. CG-90 has very low odour with a corrosion inhibitor. Food Grade CG-90 is an ideal product for lubricating locks, chains, bearing, springs, slides and gears. Food Grade CG-90 is also suitable for some plastic components in delicate systems cash machines coin operated machines. Food Grade CG-90 has a diversity of uses this will simplify stocking inventory and prevent greasing errors.

Safe for use in food preparation areas and approved to H1 standard by InS certification 1795391

14-09-2025 1/2

Clean and clearNon toxic no odour

- Reduced stick slip behaviour

Benefits

- Corrosion inhibitor built into formulation  $% \left( 1\right) =\left( 1\right) \left( 1\right) \left$
- Water, steam, acid and alkalis resistant
- Wide temperature range from -40  $^{\circ}\text{C}$  to +200  $^{\circ}\text{C}$  (applies to base product before

aerosol packing)

Food Grade ProductsBearing LubricantChain Lubricant

Application

Corrosion ProtectionGeneral LubricantPTFE Lubricant

- Plumbing Products
Properties Food Grade certified to H1 standard by InS 1795391

Consists of - 500ml Aerosol

Unit Each Content (ml) 500

14-09-2025 2/2