


CR610 Low Pressure Oil Hose 3/8"



Part No: CR610

Price: £7.13 (exc VAT) | £8.56 (inc VAT)

Specifications

CR610 Low Pressure Oil Hose 3/8"

Low pressure Oil resistant Hose

****Not suitable for use as a Hydraulic hose****

Specifications - Rubber hydraulic hose with 1 ply of high-strength fabric mesh

Benefits - Lightweight

- Flexible hose

Application - Low pressure hydraulic systems

- Mineral oil-based and glycol-based fluids

- Lubricants

- Air

- Water

Properties - Oil-resistant, smooth outer coating

Technical information - Available lengths: by the metre

- Not suitable for dynamic pressure loads

Test pressure 56 BAR

Hose material inside NBR

Ferrule type SFA-14S

Construction Hose material outside

SBR/CR-rubber

Hose material inside

NBR-rubber

Reinforcement

- braid synthetic braid

- quantity: 2

Internal Ø (inch) 3/8" in

Internal Ø (mm) 9.5 mm

Working pressure 28 BAR

Length per roll 50 m

Outside Ø (mm) 15.9 mm

DN according to DIN 10

Dn according to EN 10

Bend radius 75 mm

Burst pressure (bar) 110 BAR

Working pressure 2.8 MPa

Ferrule required 1 SFA-SK1-10

Swage diameter 1 20 mm

Number of plies 1 pcs

Material SBR / CR