

Carpenter Goodwin
31 Bridge St
Leominster
Herefordshire
HR6 8DU
01568 616266
www.carpentergoodwin.co.uk

Exol Excelfluid NP 25 Litre S007D00



Part No: S007D00

Price: £109.95 (exc VAT) | £131.94 (inc VAT)

Specifications

Exol Excelfluid NP 25 Litre S007D00

Excelfluid NP is a cost effective, non EP, milky soluble cutting fluid.

Suitable for use on both ferrous and non-ferrous materials.

It is designed for general purpose machining with good performance in both hard and soft water.

Excelfluid NP is a water-mix cutting fluid which forms a milky type emulsion when mixed with water.

This new improved version of Excelfluid NP possesses greater biostability for extended sump life, greatly improved rust protection, consistent pH in a variety of water types and improved miscibility (spontaneity) when added to water.

Excelfluid NP is suitable for a wide range of non-arduous machining operations on both ferrous and non-ferrous materials where a cost effective, general purpose coolant is required.

Benefits:

Improved rust protection

Produces a high degree of machine tool lubrication

Suitable for a wide range of machining applications

Improved sump life in comparison to more conventional milky soluble oils

27-10-2025 1/2

Low unit cost

Easy mixing when added to water

Application:

Excelfluid NP should be used at concentrations higher than its specified corrosion break point.

Maximum machining performance can be achieved at concentrations of up to 12%, however the majority of operations will be completed with concentrations in the range 5% to 10%.

27-10-2025 2/2