

Carpenter Goodwin
31 Bridge St
Leominster
Herefordshire
HR6 8DU
01568 616266
www.carpentergoodwin.co.uk

SAC05030B Compressor 50ltr V-Twin Direct



Part No: SAC05030B

Price: £259.95 (exc VAT) Save £200.00

(RRP £459.95) | £311.94 (inc VAT)

Specifications

Sealey SAC05030B Compressor 50ltr V-Twin Direct B Stock

B Stock

Shop Collection or only available for delivery to the following local Postcodes HR, WR, SY & LD.

If you are interested in this product and are outside of our local Van delivery area, please enquire with our Sales Staff on 01568 616266 or by email at sales@carpentergoodwin.co.uk for Courier delivery rates if you have a UK Mainland delivery address only, for this product.

**** THIS ITEM MAY BE SHOP SOILED AND/OR MAY HAVE SOME COSMETIC OR PACKAGING DAMAGE****

V-Twin pump with aluminium cylinders and cast iron liners for reduced weight and improved

1-12-2025 1/3

resistance to wear.

Suitable for general purpose workshop applications.

Pump directly coupled to heavy-duty induction motor for reliable operation.

Precision welded receiver tank manufactured to meet Pressure Vessel Directive.

Fitted with fully automatic pressure cut-out switch, air regulator and pressure gauges for tank and supply.

Supplied with handle and wheels for easy manoeuvrability.

Fitted with ASTA/BS approved non-rewirable plug.

Features:

Air Displacement: 12.6cfm(357L/min).

Maximum Free Air Delivery: 8.75cfm(248L/min).

Maximum Pressure: 130psi(9bar).

V-Twin pump with aluminium cylinders and cast iron liners for reduced weight and improved resistance to wear.

Suitable for general-purpose workshop applications.

Pump directly coupled to heavy-duty induction motor for reliable operation.

Precision welded receiver tank manufactured to meet Pressure Vessel Directive.

Fitted with fully automatic pressure cut-out switch, air regulator and pressure gauges for tank and supply.

Supplied with handle and wheels for easy manoeuvrability.

Fitted with 3-pin plug.

Specifications:

Air Displacement cfm(L/min): 12.6(357)

Maximum Free Air Delivery cfm(L/min): 8.75(248)

Maximum Pressure: 130psi(9bar)

1-12-2025 2/3

Minimum Rated Supply: 13A

Motor Output: 3hp

Outlet: Quick Release Coupling

Phase: 1ph

Receiver Capacity: 50L

Size (W x D x H): 810 x 420 x 620mm

Supply: 230V

1-12-2025 3/3